

# CARBOMIID®

## Functional Textiles

### Technical Datasheet

PRODUCT CODE	CM GMSH 220
PRODUCT DESCRIPTION	GLASS MESH FABRIC_ 1200 Tex _220 gr/m2

LAYER	Glass Fibre Bi-directional Mesh for Structural Reinforcement
WARP PER END	1.8 / WARP - 1200 Tex E Glass Roving Fiber + 50 Tex TP Yarn
WEFT PER END	1.8 / WEFT - 1200 Tex E Glass Roving Fiber + 50 Tex TP Yarn

#### FIBER PROPERTIES

YARN	E GLASS 1200 Tex Single End Roving
FIBER DIAMETER	17 Micron
SIZING TYPE	Silane
SIZING CONTENT (%)	0,55 ± 0,15
RESIN COMPATIBILITY	POLYESTER,VINYLESTER,EPOXY RESINS
TEST METHOD	ISO 10618

#### ROLL INFO

ROLL WEIGHT	11 KG
ROLL LENGTH	50 MT
ROLL WIDTH	100 CM

PACKAGING	ALL ROLLS ARE WRAPPED WITH PE SHEET AND IN SINGLE CARDBOARD BOXES
-----------	---

STORAGE	STORE IN A COOL AND DRY PLACES KEEP AWAY FROM DIRECT SUN LIGHT
---------	--

#### CERTIFICATION



CARBOMID FABRICS ARE PRODUCED BY BIRLIK TICARET AS WHO IS RUN BY ISO 9001:2015 QA SYSTEM

