

CARBOMID®

Functional Textiles

Technical Datasheet

| | |
|---------------------|--------------------------------|
| PRODUCT CODE | CM CP 200 |
| PRODUCT DESCRIPTION | CARBON FABRIC_ 3K Carbon Plain |

| | |
|--------------|--------------------------------------|
| LAYER | REINFORCEMENT CONSTRUCTION |
| WARP PER END | 5.0 / WARP - 200 Tex 3K CARBON FIBER |
| WEFT PER END | 5.0 / WEFT - 200 Tex 3K CARBON FIBER |

FIBER PROPERTIES



| | |
|---------------------|-----------------------------------|
| YARN | CARBON 3K - 200 Tex |
| TENSILE STRENGTH | CARBON: 3800 MPA |
| TENSILE MODULUS | CARBON: 240 GPA |
| STRAIN | CARBON: 1.6% |
| RESIN COMPATIBILITY | POLYESTER,VINYLESTER,EPOXY RESINS |
| TEST METHOD | ISO 10618 |

ROLL INFO

| | |
|-------------|--------|
| ROLL WEIGHT | 20 KG |
| ROLL LENGTH | 100 MT |
| ROLL WIDTH | 100 CM |

| | |
|-----------|---|
| PACKAGING | ALL ROLLS ARE WRAPPED WITH PE SHEET AND IN SINGLE CARDBOARD BOXES |
|-----------|---|

| | |
|---------|--|
| STORAGE | STORE IN A COOL AND DRY PLACES KEEP AWAY FROM DIRECT SUN LIGHT |
|---------|--|

| | |
|---|--|
|   | CARBOMID FABRICS ARE PRODUCED BY BIRLIK TICARET AS WHO IS RUN BY ISO 9001:2015 QA SYSTEM |
|---|--|

